



Attestation of Conformity

No. N8A 073342 0265 Rev. 00

Holder of Certificate: Sungrow Power Supply Co., Ltd.

No. 1699 Xiyou Road, New & High Technology Industrial Development Zone, 230088 Hefei, Anhui PEOPLE'S REPUBLIC OF CHINA

Product:

Converter PV Grid-connected Inverter

This Attestation of Conformity is issued on a voluntary basis according to the Low Voltage Directive 2014/35/EU relating to electrical equipment designed for use within certain voltage limits. It confirms that the listed equipment complies with the principal protection requirements of the directive and is based on the technical specifications applicable at the time of issuance.

It refers only to the particular sample submitted for testing and certification. See also notes overleaf.

Test report no.:

704091802546-00

Date,

2019-03-21

(Zhengdong Ma)

Page 1 of 2

After preparation of the necessary technical documentation as well as the EU declaration of conformity the required CE marking can be affixed on the product. The declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.

A4 / 07.17





Attestation of Conformity

No. N8A 073342 0265 Rev. 00

Model(s):

SG150TX, SG136TX, SG132TX, SG110CX, SG100CX.

Parameters:

d.c. 9×26 A (SG110CX, SG100CX), Isc PV: d.c. 12×40 A (SG150TX, SG136TX, SG132TX), d.c. 9×40 A (SG110CX, SG100CX), Nominal grid voltage: a.c. 3/PE ~ 540V (SG150TX, SG136TX), a.c. 3/PE ~ 480V (SG132TX), a.c. 3/N/PE ~ 400/230V (SG110CX, SG100CX) Nominal grid frequency: 50/60Hz Max. continuous output current:		
Max. MPP voltage: d.c. 1000 V Max. input current: d.c. 12×26 A (SG150TX, SG136TX, SG132TX) d.c. 9×26 A (SG110CX, SG100CX), Isc PV: d.c. 12×40 A (SG150TX, SG136TX, SG132TX) d.c. 9×40 A (SG110CX, SG100CX), Nominal grid voltage: a.c. 3/PE ~ 540V (SG150TX, SG136TX), a.c. 3/PE ~ 480V (SG132TX), a.c. 3/N/PE ~ 400/230V (SG110CX, SG100CX) Nominal grid frequency: 50/60Hz Max. continuous output current: a.c. 160.4 A (SG150TX, SG136TX), a.c. 158.8 A (SG132TX, SG110CX, SG100CX) Rated output power: 136 kW (SG150TX, SG136TX), 120 kW (SG132TX), 100 kW (SG132TX), 100 kW (SG110CX, SG100CX) Max. apparent power: 150 kVA (SG150TX, SG136TX), 132 kVA (SG132TX), 110 kVA (SG110CX, SG100CX) Power factor range: 0.8Leading0.8Lagging Ambient temperature range: -30°C+60°C Protective class: 1 Ingress protection: IP66	Vmax PV:	d.c. 1100 V
Max. input current: d.c. 12×26 A (SG150TX, SG136TX, SG132TX) d.c. 9×26 A (SG110CX, SG100CX), Isc PV: d.c. 12×40 A (SG150TX, SG136TX, SG132TX) d.c. 9×40 A (SG110CX, SG100CX), Nominal grid voltage: a.c. 3/PE ~ 540V (SG150TX, SG136TX), a.c. 3/PE ~ 480V (SG132TX), a.c. 3/N/PE ~ 400/230V (SG110CX, SG100CX) Nominal grid frequency: 50/60Hz Max. continuous output current: a.c. 160.4 A (SG150TX, SG136TX), a.c. 158.8 A (SG132TX, SG110CX, SG100CX) Rated output power: 136 kW (SG150TX, SG136TX), 120 kW (SG132TX), 100 kW (SG110CX, SG100CX) Max. apparent power: 150 kVA (SG150TX, SG136TX), 122 kVA (SG132TX), 100 kW (SG110CX, SG100CX) Power factor range: 0.8Leading08Lagging Ambient temperature range: -30°C+60°C Protective class: I Ingress protection: IP66	Min. MPP voltage:	d.c. 200 V
d.c. 9×26 A (SG110CX, SG100CX),Isc PV:d.c. 12×40 A (SG150TX, SG136TX, SG132TX) d.c. 9×40 A (SG110CX, SG100CX),Nominal grid voltage:a.c. 3/PE ~ 540V (SG150TX, SG136TX), a.c. 3/PE ~ 480V (SG132TX), a.c. 3/N/PE ~ 400/230V (SG110CX, SG100CX)Nominal grid frequency:50/60HzMax. continuous output current:a.c. 160.4 A (SG150TX, SG136TX), a.c. 158.8 A (SG132TX, SG110CX, SG100CX)Rated output power:136 kW (SG150TX, SG136TX), 120 kW (SG132TX), 100 kW (SG110CX, SG100CX)Max. apparent power:150 kVA (SG150TX, SG136TX), 132 kVA (SG132TX), 110 kVA (SG110CX, SG100CX)Power factor range:0.8Leading0.8LaggingAmbient temperature range:-30°C+60°CProtective class:IIngress protection:IP66	Max. MPP voltage:	d.c. 1000 V
d.c. 9×40 A (SG110CX, SG100CX),Nominal grid voltage:a.c. 3/PE ~ 540V (SG150TX, SG136TX), a.c. 3/PE ~ 480V (SG132TX), a.c. 3/N/PE ~ 400/230V (SG110CX, SG100CX)Nominal grid frequency:50/60HzMax. continuous output current:a.c. 160.4 A (SG150TX, SG136TX), a.c. 158.8 A (SG132TX, SG110CX, SG100CX)Rated output power:136 kW (SG150TX, SG136TX), 120 kW (SG150TX, SG136TX), 120 kW (SG132TX), 100 kW (SG110CX, SG100CX)Max. apparent power:150 kVA (SG150TX, SG136TX), 132 kVA (SG132TX), 110 kVA (SG110CX, SG100CX)Power factor range:0.8Leading0.8LaggingAmbient temperature range:-30°C+60°CProtective class:IIngress protection:IP66	Max. input current:	d.c. 12×26 A (SG150TX, SG136TX, SG132TX) d.c. 9×26 A (SG110CX, SG100CX),
a.c. 3/PE ~ 480V (SG132TX), a.c. 3/N/PE ~ 400/230V (SG110CX, SG100CX)Nominal grid frequency:50/60HzMax. continuous output current:a.c. 160.4 A (SG150TX, SG136TX), a.c. 158.8 A (SG132TX, SG110CX, SG100CX)Rated output power:136 kW (SG150TX, SG136TX), 120 kW (SG150TX, SG136TX), 120 kW (SG132TX), 100 kW (SG110CX, SG100CX)Max. apparent power:150 kVA (SG150TX, SG136TX), 132 kVA (SG132TX), 110 kVA (SG110CX, SG100CX)Power factor range:0.8Leading0.8LaggingAmbient temperature range:-30°C+60°CProtective class:IIngress protection:IP66	Isc PV:	d.c. 12×40 A (SG150TX, SG136TX, SG132TX) d.c. 9×40 A (SG110CX, SG100CX),
Max. continuous output current:a.c. 160.4 A (SG150TX, SG136TX), a.c. 158.8 A (SG132TX, SG110CX, SG100CX)Rated output power:136 kW (SG150TX, SG136TX), 120 kW (SG132TX), 100 kW (SG110CX, SG100CX)Max. apparent power:150 kVA (SG150TX, SG136TX), 	Nominal grid voltage:	
a.c. 158.8 A (SG132TX, SG110CX, SG100CX)Rated output power:136 kW (SG150TX, SG136TX), 120 kW (SG132TX), 100 kW (SG110CX, SG100CX)Max. apparent power:150 kVA (SG150TX, SG136TX), 132 kVA (SG132TX), 110 kVA (SG110CX, SG100CX)Power factor range:0.8Leading0.8LaggingAmbient temperature range:-30°C+60°CProtective class:IIngress protection:IP66	Nominal grid frequency:	50/60Hz
120 kW (SG132TX), 100 kW (SG110CX, SG100CX)Max. apparent power:150 kVA (SG150TX, SG136TX), 132 kVA (SG132TX), 110 kVA (SG110CX, SG100CX)Power factor range:0.8Leading0.8LaggingAmbient temperature range:-30°C+60°CProtective class:IIngress protection:IP66	Max. continuous output current:	a.c. 160.4 A (SG150TX, SG136TX), a.c. 158.8 A (SG132TX, SG110CX, SG100CX)
132 kVA (SG132TX), 110 kVA (SG110CX, SG100CX) Power factor range: 0.8Leading0.8Lagging Ambient temperature range: -30°C+60°C Protective class: I Ingress protection: IP66	Rated output power:	120 kW (SG132TX),
Ambient temperature range: -30°C+60°C Protective class: I Ingress protection: IP66	Max. apparent power:	132 kVA (SG132TX),
Protective class: I Ingress protection: IP66	Power factor range:	0.8Leading0.8Lagging
Ingress protection: IP66	Ambient temperature range:	-30°C+60°C
	Protective class:	
Overvoltage category: II(PV), III(Mains)	Ingress protection:	IP66
	Overvoltage category:	II(PV), III(Mains)

Tested according to:

EN 62109-1:2010 EN 62109-2:2011

Page 2 of 2

Xh was

After preparation of the necessary technical documentation as well as the EU declaration of conformity the required CE marking can be affixed on the product. The declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.